

## ELEVATE YOUR PACKAGING CAPABILITIES WITH PRINT & APPLY APPLICATORS

### The 3600a-PA Printer-Applicator

The 3600a OA Printer-Applicator is a rugged and versatile, high-speed, thermal transfer labeler used to print and apply pressure sensitive labels to various products. Available in CE versions.

**Features:** Features include Heavy Duty Construction, Tamp Blow Applicator, External Valves and Controls, Remote Operator Color, Touchscreen Display 12" O.D. Label Roll, 1/0 Connection and Communication Port Connections.

Optional features include: Low Label/Low Ribbon, Out of Label/Out of Ribbon, End of Web, Red, Amber and Green "Ready" Stack Lights and 16" Unwind and High Capacity Rewind for large label rolls.

#### Electrical

108-132 Volts AC, 5 Amps, 50/60 Hertz, Single Phase

#### Pneumatic

90 psi., 3-5 CFM

#### Communications

RS2 32, Parallel, Ethernet, USB or Wireless

#### Environmental

Operating: 41° F to 104° F (5° C to 40° C)

Storage: -4° F to 104° F (-20° C to 40° C)

#### Printing Methods

Thermal Transfer & Direct Thermal

#### Dimensions

31.5' L X 27.5' W X 23 5' H

#### Weight

Approx. 50 lbs.

### WHY CHOOSE FORTIS?

- All techs are fully trained and certified by each manufacturer: Sato, Zebra, CTM, etc.
- Consistent and accurate label application time and time again
- Save space; small footprint with options to integrate into existing lines
- Opportunities to finance applicators through our labels BOOST program



## The 3600a-PA Corner Wrap Printer-Applicator

The 3600a-PA Corner Wrap Printer-Applicator is a rugged and versatile, high-speed, thermal transfer/direct thermal labeler used to print and apply pressure sensitive labels to the leading and side panels of various cartons, cases or pallets.

### Electrical/Pneumatic

108-132 Volts AC, 50/60 Hertz, Single Phase, 5 Amps., Clean, Dry air, 90 PSI., Approx. 3-5 CMF

### Environmental

Operating: 41° F to 104° F (5° C to 40° C)

Storage: -4° F to 105° F (-20° C to 40° C)

### Optional Features

Low label, Low Ribbon, End of Web, End of Ribbon Stack light (silent or audible)

Allen-Bradley PLC

Consult CTM Labeling Systems for other options

### Weight

Approx 120 lbs.



## The 3600-PA Dual Action Tamp (DAT) Printer-Applicator

The 3600-PA Dual Action Tamp (DAT) Printer Applicator is a high-speed, thermal transfer labeler used to print and apply pressure sensitive labels.

### Electrical

108-132 Volts AC, 5 Amps, 54/60 Hertz, Single Phase

### Pneumatic

90 PSI., 3-5 CMF

### Communications

RS 232, Parallel-Others Available

### Environmental

Operating: 41° F to 104° F (5° C to 40° C)

Storage: -4° F to 104° F (-20° C to 40° C)

### Printing Methods

Thermal Transfer, Direct Thermal

### Dimensions

Dependent Upon Line Configuration

### Weight

Approx. 150 lbs.



## Contact Us Today

for a site survey so we can determine the perfect Applicator for your needs!

Reach out to your Fortis Solutions Group Representative.

Or call: **1-844-765-8867**

**applicators@fortissolutionsgroup.com**

**fortissolutionsgroup.com**

© Fortis Solutions Group, 9/25